



**UNI-ROYAL**  
厚聲集團

# DATA SHEET

**Product Name** High Voltage Thick Film Chip Resistors

---

**Part Name** HV Series

**File No.** SMD-0SP-005

## Uniroyal Electronics Global Co., Ltd.

88#, Longteng Road, Economic & Technical Development Zone, Kunshan, Jiangsu, China

Tel +86 512 5763 1411 / 22 /33

Email [marketing@uni-royal.cn](mailto:marketing@uni-royal.cn)

Manufacture Plant Uniroyal Electronics Industry Co., Ltd.  
Aeon Technology Corporation  
Royal Electronic Factory (Thailand) Co., Ltd.  
Royal Technology (Thailand) Co., Ltd.

## 1. Scope

- 1.1 This data sheet is the characteristics of High Voltage Thick Film Chip Resistors manufactured by UNI-ROYAL.
- 1.2 The performance in Max. Working Voltage is superior to the general thick film chip resistors.
- 1.3 Suitable for reflow & wave soldering
- 1.4 AEC-Q200 qualified
- 1.5 Applications: AV adapters, LCD backlight, Camera flash, etc.

## 2. Part No. System

Part No. includes 14 codes shown as below:

2.1 1<sup>st</sup>~4<sup>th</sup> codes: Part name. E.g.: HV03, HV05, HV06, HV07, HV10, HV12

2.2 5<sup>th</sup>~6<sup>th</sup> codes: Power rating.

E.g.: W=Normal Size                      "1~G" = "1~16"

Wattage	1/32	3/4	1/2	1/3	1/4	1/8	1/10	1/16	1/20	1
Normal Size	WH	07	W2	W3	W4	W8	WA	WG	WM	1W

If power rating is equal or lower than 1 watt, 5<sup>th</sup> code would be "W" and 6<sup>th</sup> code would be a number or letter.

E.g.: WA=1/10W                      W4=1/4W

2.3 7<sup>th</sup> code: Tolerance. E.g.: F=±1%

J=±5%

2.4 8<sup>th</sup>~11<sup>th</sup> codes: Resistance value.

2.4.1 If value belongs to standard value of E-24 series, the 8<sup>th</sup> code is zero, 9<sup>th</sup>~10<sup>th</sup> codes are the significant figures of resistance value, and the 11<sup>th</sup> code is the power of ten.

2.4.2 If value belongs to standard value of E-96 series, the 8<sup>th</sup>~10<sup>th</sup> codes are the significant figures of resistance value, and the 11<sup>th</sup> code is the power of ten.

2.4.3 11<sup>th</sup> codes listed as following:

0=10<sup>0</sup>    1=10<sup>1</sup>    2=10<sup>2</sup>    3=10<sup>3</sup>    4=10<sup>4</sup>    5=10<sup>5</sup>    6=10<sup>6</sup>    J=10<sup>-1</sup>    K=10<sup>-2</sup>    L=10<sup>-3</sup>    M=10<sup>-4</sup>

2.5 12<sup>th</sup>~14<sup>th</sup> codes.

2.5.1 12<sup>th</sup> code: Packaging Type. E.g.: T=Tape/Reel

2.5.2 13<sup>th</sup> code: Standard Packing Quantity.


4=4,000pcs                      5=5,000pcs

2.5.3 14<sup>th</sup> code: Special features.

E = Environmental Protection, Lead Free, or Standard type.

## 3. Ordering Procedure

(Example: HV06 1/4W ±1% 100KΩ T/R-5000)



## 4. Marking

### 3.1 ±5% tolerance products (E-24 series):

3 codes.

1<sup>st</sup>~2<sup>nd</sup> codes are the significant figures of resistance value, and the rest code is the power of ten.



104 → 100KΩ

### 3.2 ±1% tolerance products (E-96 series):

4 codes.

1<sup>st</sup>~3<sup>rd</sup> codes are the significant figures of resistance value, and the rest code is the power of ten.

Letter "R" in mark means decimal point.



1003 → 100KΩ

### 3.3 Standard E-96 series values of 0603 ≤ 1% : due to the small size of the resistor's body, 3 digits marking will be used to indicate the accurate resistance value by using the following multiplier & resistance code.

Multiplier Code (for 0603 ≤ ±1% marking)

Code	A	B	C	D	E	F	G	H	X	Y	Z
Multiplier	10 <sup>0</sup>	10 <sup>1</sup>	10 <sup>2</sup>	10 <sup>3</sup>	10 <sup>4</sup>	10 <sup>5</sup>	10 <sup>6</sup>	10 <sup>7</sup>	10 <sup>-1</sup>	10 <sup>-2</sup>	10 <sup>-3</sup>

Standard E-96 series Resistance Value code (for 0603 ≤ ±1% marking)

Value	Code	Value	Code	Value	Code	Value	Code
100	01	178	25	316	49	562	73
102	02	182	26	324	50	576	74
105	03	187	27	332	51	590	75
107	04	191	28	340	52	604	76
110	05	196	29	348	53	619	77
113	06	200	30	357	54	634	78
115	07	205	31	365	55	649	79
118	08	210	32	374	56	665	80
121	09	215	33	383	57	681	81
124	10	221	34	392	58	698	82
127	11	226	35	402	59	715	83
130	12	232	36	412	60	732	84
133	13	237	37	422	61	750	85
137	14	243	38	432	62	768	86
140	15	249	39	442	63	787	87
143	16	255	40	453	64	806	88
147	17	261	41	464	65	825	89
150	18	267	42	475	66	845	90
154	19	274	43	487	67	866	91
158	20	280	44	499	68	887	92
162	21	287	45	511	69	909	93
165	22	294	46	523	70	931	94
169	23	301	47	536	71	953	95
174	24	309	48	549	72	976	96

So the resistance value are marked as the following examples



1.96KΩ=196×10<sup>1</sup>Ω=29B



12.4Ω=124×10<sup>-1</sup>Ω=10X

3.4 Standard E-24 and not belong to E-96 series values ( $\leq \pm 1\%$ ) of 0603 size: the marking is the same as 5% tolerance but marking as underline.




333=33K $\Omega$



680=68 $\Omega$

## 5. Dimension

Type	Dimension(mm)				
	L	W	H	A	B
HV03(0603)	1.60 $\pm$ 0.10	0.80 $\pm$ 0.10	0.45 $\pm$ 0.10	0.30 $\pm$ 0.20	0.30 $\pm$ 0.20
HV05(0805)	2.00 $\pm$ 0.15	1.25 $^{+0.15}_{-0.10}$	0.55 $\pm$ 0.10	0.40 $\pm$ 0.20	0.40 $\pm$ 0.20
HV06(1206)	3.10 $\pm$ 0.15	1.55 $^{+0.15}_{-0.10}$	0.55 $\pm$ 0.10	0.45 $\pm$ 0.20	0.45 $\pm$ 0.20
HV07(1210)	3.10 $\pm$ 0.10	2.60 $\pm$ 0.20	0.55 $\pm$ 0.10	0.50 $\pm$ 0.25	0.50 $\pm$ 0.20
HV10(2010)	5.00 $\pm$ 0.10	2.50 $\pm$ 0.20	0.55 $\pm$ 0.10	0.60 $\pm$ 0.25	0.50 $\pm$ 0.20
HV12(2512)	6.35 $\pm$ 0.10	3.20 $\pm$ 0.20	0.55 $\pm$ 0.10	0.60 $\pm$ 0.25	0.50 $\pm$ 0.20




## 6. Ratings

Type	Power Rating at 70 $^{\circ}$ C	Max. Working Voltage	Max. Overload Voltage	Dielectric withstanding Voltage	Resistance Range	Operating Temperature
HV03	1/10W	200V	400V	300V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C
HV05	1/8W	400V	800V	500V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C
HV06	1/4W	500V	1000V	500V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C
HV07	1/2W	800V	1500V	500V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C
HV10	3/4W	2000V	3000V	500V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C
HV12	1W	3000V	4000V	500V	47 $\Omega$ ~10M $\Omega$	-55 $^{\circ}$ C~155 $^{\circ}$ C

## 7. Soldering pad size recommended

Type	Dimension(mm)			
	A	B	C	D
HV03	0.8 $\pm$ 0.05	0.65 $\pm$ 0.05	0.8 $\pm$ 0.05	2.1 $\pm$ 0.05
HV05	1.0 $\pm$ 0.1	1.0 $\pm$ 0.1	1.3 $\pm$ 0.1	3.0 $\pm$ 0.1
HV06	2.2 $\pm$ 0.1	1.1 $\pm$ 0.1	1.6 $\pm$ 0.1	4.4 $\pm$ 0.1
HV07	2.1 $\pm$ 0.1	1.1 $\pm$ 0.1	2.6 $\pm$ 0.1	4.4 $\pm$ 0.1
HV10	3.6 $\pm$ 0.1	1.3 $\pm$ 0.1	2.6 $\pm$ 0.1	6.2 $\pm$ 0.1
HV12	5.0 $\pm$ 0.1	1.6 $\pm$ 0.1	3.3 $\pm$ 0.1	8.2 $\pm$ 0.1



## 8 Derating Curve

Power rating will change based on continuous load at ambient temperature from -55 to 155°C. It is constant between -55 to 70°C, and derate to zero when temperature rise from 70 to 155°C.

Voltage rating:


Resistors shall have a rated direct-current (DC) continuous working voltage or an approximate sine-wave root-mean-square (RMS) alternating-current (AC) continuous working voltage at commercial-line frequency and waveform corresponding to the power rating, as determined from the following formula:

$$RCWV = \sqrt{P} \times R$$


Remark: RCWV: Rating Continuous Working Voltage (Volt.) P: power rating (Watt) R: nominal resistance (Ω)

In no case shall the rated DC or RMS AC continuous working voltage be greater than the applicable maximum value.

The overload voltage is 2.5 times RCWV or Max. Overload voltage whichever is lower.



## 9 Structure



## 10 Performance Specification


Characteristic	Limits	Ref. Standards	Test Methods
Operational life	±(3.0%+0.1Ω)	MIL-STD-202	125°C, at 36% of operating power, 1000H(1.5 hours "ON", 0.5 hour "OFF").
Electrical Characterization	±100PPM/°C	GB/T 5729 4.8 JIS-C-5201 4.8 IEC60115-1 4.8	Natural resistance changes per temp. Degree centigrade $\frac{R_2 - R_1}{R_1(t_2 - t_1)} \times 10^6 \text{ (PPM/°C)}$ R <sub>1</sub> : Resistance Value at room temperature t <sub>1</sub> R <sub>2</sub> : Resistance at test temperature (t <sub>2</sub> ) t <sub>1</sub> : Room temperature +25°C or specified t <sub>2</sub> : Test temperature (-55°C or 125°C)
Short-time overload	±(2.0%+0.1Ω)	GB/T 5729 4.13 JIS-C-5201 4.13 IEC60115-1 4.13	Permanent resistance change after the application of a potential of 2.5 times RCWV or Max. Overload Voltage whichever less for 5 seconds..
External Visual	No Mechanical Damage	MIL-STD-883 Method 2009	Electrical test not required. Inspect device construction, marking and workmanship
Physical Dimension	Reference 5 Dimension Standards	JESD22 MH Method JB-100	Verify physical dimensions to the applicable device detail specification. Note: User(s) and Suppliers spec. Electrical test not required.
Resistance to Solvent	Marking Unsmeared	MIL-STD-202 Method 215	Note: Add Aqueous wash chemical – OKEM Clean or equivalent. Do not use banned solvents.
Terminal Strength	Not broken	JIS-C-6429	Force of 1.8kg for 60 seconds.
High Temperature Exposure (Storage)	±(3.0%+0.1Ω)	MIL-STD-202 Method 108	1000hrs. @T=155°C. Unpowered. Measurement at 24±2 hours after test conclusion.
Temperature Cycling	5%: ±(3.0%+0.1Ω)	JESD22 Method JA-104	1000 Cycles (-55°C to +125°C). Measurement at 24±2 hours after test conclusion.
	1% : ±(1%+0.1Ω)		

Biased Humidity	$\pm(3.0\%+0.1\Omega)$	MIL-STD-202 Method 103	1000 hours 85 °C, 85%RH. Note: Specified conditions: 10% of operating power. Measurement at 24 $\pm$ 2 hours after test conclusion.
Mechanical Shock	$\pm(1.0\%+0.1\Omega)$	MIL-STD-202 Method 213	Wave Form: Tolerance for half sine shock pulse. Peak value is 100g's. Normal duration (D) is 6ms, velocity 12.3ft/s 100Hz.
Vibration	$\pm(1.0\%+0.1\Omega)$	MIL-STD-202 Method 204	5g's for 20 min., 12cycle each of 3 orientations. Note: Use 8''*5''PCB. 031'' thick 7 secure points on one long side and 2 secure points at corners of opposite sides. Parts mounted within 2' from any secure point. Test from 10-2000Hz.
ESD	$\pm(3.0\%+0.1\Omega)$	AEC-Q200-002	Test condition: 150PF 2K 1 pos. + 1 neg. discharges HV03~HV05: 1kV HV06 and above: 2kV
Solderability	Coverage must be over 95%.	J-STD-002	For both leaded & SMD. Electrical test not required. Magnification 50X. Conditions: a) Method B 4hrs at 155 °C dry heat, the dip in bath with 245 $\pm$ 3 °C, 5 $\pm$ 0.5s. b) Method D: at 260 $\pm$ 3 °C, 30 $\pm$ 0.5s.
Flammability	No ignition of the tissue paper or scorching or the pinewood board	UL-94	V-0 or V-1 are acceptable. Electrical test not required.
Board Flex	$\pm(1.0\%+0.1\Omega)$	JIS-C-6429	Bending 3mm(HV03-HV05)/2mm(HV06-HV12)for 60 $\pm$ 5sec
Flame Retardance	No flame	AEC-Q200-001	Only requested, when voltage/power will increase the surface temp to 350 °C. Apply voltage from 9V to 32V. No flame; No explosion.
Resistance to Soldering Heat	$\pm(1.0\%+0.1\Omega)$	MIL-STD-202 Method 210	Condition B No per-heat of samples. Dipping the resistor into a solder bath having a temperature of 260 °C $\pm$ 5 °C and hold it for 10 $\pm$ 1 seconds

## 11. Soldering Condition

(This is for recommendation, please customer perform adjustment according to actual application)

11.1 Recommend Reflow Soldering Profile : (solder : Sn96.5 / Ag3 / Cu0.5)




Profile Feature	Lead (Pb)-Free solder
Preheat: Temperature Min (T <sub>smin</sub> ) Temperature Max (T <sub>smax</sub> ) Time (T <sub>smin</sub> to T <sub>smax</sub> ) (t <sub>s</sub> )	150°C 200°C 60 -120 seconds
Average ramp-up rate: (T <sub>smax</sub> to T <sub>p</sub> )	3°C / second max.
Time maintained above : Temperature (T <sub>L</sub> ) Time (t <sub>L</sub> )	217°C 60-150 seconds
Peak Temperature (T <sub>p</sub> )	260°C
Time within $\begin{matrix} +0 \\ -5 \end{matrix}$ °C of actual peak Temperature (t <sub>p</sub> ) <sup>2</sup>	10 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8minutes max.

Allowed Re-flow times : 2 times

Remark : To avoid discoloration phenomena of chip on terminal electrodes, please use N2 Re-flow furnace .


11.2 Recommend Wave Soldering Profile : (Apply to 0603 and above size)



## 12. Packing


### 12.1 Dimension of Paper Taping: (Unit: mm)

Type	A ±0.2	B ±0.2	C ±0.05	ΦD $^{+0.1}_0$	E ±0.1	F ±0.05	G ±0.1	W ±0.2	T ±0.1
HV03	1.10	1.90	2.00	1.50	1.75	3.50	4.00	8.00	0.67
HV05	1.65	2.40	2.00	1.50	1.75	3.50	4.00	8.00	0.81
HV06	2.00	3.60	2.00	1.50	1.75	3.50	4.00	8.00	0.81
HV07	2.80	3.50	2.00	1.50	1.75	3.50	4.00	8.00	0.75




### 12.2 Dimension of plastic taping (Unit: mm)

Type	A ±0.2	B ±0.2	C ±0.05	ΦD $^{+0.1}_0$	ΦD1 $^{+0.25}_0$	E ±0.1	F ±0.05	G ±0.1	W ±0.2	T ±0.1
HV10	2.90	5.60	2.00	1.50	1.50	1.75	5.50	4.00	12.00	1.00
HV12	3.50	6.70	2.00	1.50	1.50	1.75	5.50	4.00	12.00	1.00



### 12.3 Dimension of Reel : (Unit: mm)

Type	Taping	Qty./Reel	A ±0.5	B ±0.5	C ±0.5	D ±1	M ±2	W ±1
HV03	Paper	5,000pcs	2.0	13.0	21.0	60.0	178.0	10.0
HV05	Paper	5,000pcs	2.0	13.0	21.0	60.0	178.0	10.0
HV06	Paper	5,000pcs	2.0	13.0	21.0	60.0	178.0	10.0
HV07	Paper	5,000pcs	2.0	13.0	21.0	60.0	178.0	10.0
HV10	Embossed	4,000pcs	2.0	13.0	21.0	60.0	178.0	13.8
HV12	Embossed	4,000pcs	2.0	13.0	21.0	60.0	178.0	13.8



## 13. Note

13.1 UNI-ROYAL recommend products store in warehouse with temperature between 15 to 35°C under humidity between 25 to 75%RH.

Even under storage conditions recommended above, solder ability of products will be degraded stored over 1 year old.

13.2 Cartons must be placed in correct direction which indicated on carton, otherwise the reel or wire will be deformed.

13.3 Storage conditions as below are inappropriate:

- Stored in high electrostatic environment
- Stored in direct sunshine, rain, snow or condensation.
- Exposed to sea wind or corrosive gases, such as Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, NO<sub>2</sub>, etc.

## 14. Record

Version	Description	Page	Date	Amended by	Checked by
1	First version	1~6	Jun.03, 2020	Song Nie	Yuhua Xu
2	Update Performance Specification	5~6	Oct.24, 2022	Song Nie	Haiyan Chen
3	Extend Resistance Range	4	Jul.12, 2023	Fucong Liu	Haiyan Chen